






## ZDACF33

### Fingerprint Standalone

#### Features

- มีปุ่มกดระบบสัมผัสและหน้าจอ LCD
- รองรับบัตร 30,000 ใบ, ลายนิ้วมือ 3,000 ลายนิ้วมือ และรหัสผ่าน
- บันทึกได้ 150,000 รายการ
- รองรับบัตรได้หลายคลื่นความถี่ EM card (125 KHz)
- เชื่อมต่อ PC ผ่าน TCP/IP
- สามารถเพิ่ม Reader ผ่าน Wiegand หรือ RS-485
- อุปกรณ์สามารถต่อกับชุด Electric lock, Exit button, Door sensor, Alarm และ Door Bell ได้
- สามารถตั้ง Anti-passback
- รองรับการตั้งตารางเวลาได้ 128 รายการ
- มี Software IMS บริหารจัดการข้อมูล



#### Technical Specification

##### System

Main Processor	32 Bit
Memory	16M

##### Input/Output Ports

Input	Door sensor x 1, Exit button x 1, Alarm input x 1
Output	Relay x 4 (Door lock, Bell, Alarm x 2)

##### Card Read

Read Format	125KHz(ID card)
Read Range	3-8cm (max.)
Response Time	<0.1s

##### Fingerprint Read

Response Time	≤0.5s
Recognition Time	≤1.5s
FAR	≤0.00004%
FRR	≤0.15%

##### Capacity

Card holders	30,000
Events	150,000
Fingerprint	3,000

##### Function

Access control	Anti-passback, Multi-door interlock, Multi-card unlock
User Management	General, VIP, Guest, Patrol, Black list, Duress
Alarm Function	Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm
Schedule Setting	Support 128 groups of schedule, 128 groups of period and 128 groups of holiday period

##### Interface

To PC	RJ45(10/100M)
To Reader	Wiegand/ RS485

##### General

RTC	Yes
Voice Prompt	Yes
Beep Tone	Buzzer
Keyboard	Sensitive touch keypad with blue backlight
Power Supply	9-15DC/200mA
Working Environment	-30°C~+60°C
Working Humidity	≤95%
Dimension(W×D×H)	192mm*32mm *160mm
Weight	0.7Kg