

# ZDD104A, ZDD108A, ZDD116A

4/8/16 Channel MHD 720P Intelligent Digital Video Recorder



## Features

- Embedded processor
- Support HDCVI/CVBS/HDTVI/AHD video inputs
- Max 5/10/18 channels IP camera inputs, each channel up to 5MP (2MP for 4ch)
- Max 20/40/72Mbps Incoming Bandwidth
- Long transmission distance over coax cable
- Support 1 SATA HDD, up to 6TB



### Technical Specification

#### System

Main Processor	Embedded Processor
Operating System	Embedded LINUX

#### Display

Interface	1 HDMI, 1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Multi-screen Display	4CH: 1/4/6 8CH: 1/4/8/9/16 16CH: 1/4/8/9/16/25
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

#### Video Detection and Alarm

Trigger Events	Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Camera Blank

#### Playback and Backup

Playback	4CH: 1/4 8CH: 1/4/9 16CH: 1/4/9/16
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network

#### Storage

Internal HDD	1 SATA Port, up to 6TB capacity for each disk
HDD Mode	Single

#### Auxiliary Interface

USB	2 USB Ports (2 USB 2.0)
RS485	1 Port, for PTZ Control

#### Third-party Support

Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more
---------------------	---

#### Audio and Video

HDCVI Camera Input	4/8/16 Channel
IP Camera Input	4+1/8+2/16+2 Channel, each channel up to 5MP
Audio In/Out	1/1
Two-way Talk	1 Channel Input, 1 Channel Output, RCA

#### Recording

Compression	H.264
Resolution	720P, 960H, D1, HD1, BCIF, CIF, QCIF
Record Rate	Main Stream: 720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Sub stream:D1/CIF/QCIF(1~25/30fps)
Bit Rate	32Kbps ~ 6144Kbps Per Channel
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval	1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec

#### Network

Interface	1 RJ-45 Port (100M)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search (Support Dahua IP camera, DVR, NVS, etc.)
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 2.4.1, CGI Conformant

#### Electrical

Power Supply	DC12V/2A
Power Consumption	<15W (Without HDD)

#### Environmental

Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
Storage Conditions	0°C ~ +50°C (+32°F ~ +122°F), 0 ~ 90% RH

#### Construction

Dimensions	Compact 1U, 260×236×48mm(10.2"×9.3"×1.9")
Net Weight	0.75kg (1.7lb) (without HDD)
Gross Weight	1.5kg (3.3lb)
Installation	Desktop installation

#### Certifications

Certifications	FCC
	UL